

EXCENOL

Polyols Polyols for Flexible Foams

Product	Polymer	Properties			Application (suitable for)
		OH Value (mgK OH/g)	Viscosity (mPa·s at 25°C)	Appearance	
910	AN	28	3,100	Yellow-Brown	Semi-rigid Foam HR Moulded Foam Hot Moulded Foam
923	AN/ST	24	5,000	Whiteish-Yellow	Semi-rigid Foam HR Moulded Foam
941WF	AN/ST	32	5,100	Creamy-White	Flexible Slabstock Foam

Note : The values shown above are typical values, not guaranteed values.

The above technical data is correct at time of going to print: 1 November 2014.
Please contact AGC for further updates and the latest information.
AGC reserves the right to revise its product range at any time without prior notice.

AGC CHEMICALS
Polyurethanes Division
Shin-Marunouchi Bldg
1-5-1, Marunouchi Chiyoda-ku
TOKYO 100-8405 JAPAN
Tel: +81-3-3218-5404
Fax: +81-3-3218-7845
Email : info-agchp@agc.co.jp
www.agc.com

AGC CHEMICALS AMERICA/AGC CHEMICALS EUROPE, LTD.
55 East Uwchlan Avenue,
Suite 201, Exton PA 19341
USA
Tel: +1-610-423-4300
Fax: +1-610-423-4301
Email : info-agcchem.com
www.agcchem.com

AGC CHEMICALS EUROPE, LTD.
Commercial Centre
Zuidplein 80
1077 VX Amsterdam, The Netherlands
Tel: +31 (0) 20 880 4170
Fax: +31 (0) 20 880 4188
Email : enquiries@agcce.com
www.agcce.com